


**C Language Programming: Homework #9**  
**Assigned on 12/19/2017(Tuesday), Due on 01/09/2018 (Tuesday)**

1. Write a program that reads data from a file containing a datum called prefix in each line of the file called **routing\_table**. Each prefix has the format of IP/length as following examples:  
0.2.64.0/15  
0.3.8.0/22  
1.3.33.0  
1.3.38.0/23
2. The first part a.b.c.d is a 32-bit IP address. So, you have to store the IP address into an unsigned variable. For prefix length, you can use an unsigned character. So, for all the prefixes, you can use an array of *struct prefix {unsigned ip; unsigned char len; struct prefix \*next;}* to store all the prefixes. Assume prefix 0.0.0.0/0 does not exist.
3. Do the following,
  - (a) write a function *input(..)* to read all the prefixes from the input file
  - (b) print out the total number of prefixes in the input file,
  - (c) write a function *length\_distribution(..)* to compute the number of prefixes with prefix length  $i$ , for  $i = 0$  to 32,
  - (d) write a function *segment(int d)* to divide the prefixes into  $2^d$  groups such that the prefixes in the same group have the same first  $d$  bits.
  - (e) Now, the prefix of length  $< d$  are put in a special group so that no prefix duplicate is created.
  - (f) printout the number of prefixes in group  $i$  for  $i = 0$  to  $2^d - 1$ .
  - (g) For each group, you have to use singly linked list to chain the prefixes together.
  - (h) Therefore, you have to write a function *prefix\_insert()* to insert a prefix in a one-by-one fashion in the increasing order of the unsigned numbers of the prefixes. The prefixes to be inserted after the segments are built are from a file called **inserted\_prefixes**.
  - (i) Also, you have to write a function *prefix\_delete()* to insert a prefix. The prefixes to be deleted after inserting all the prefixes from files **routing\_table** and **inserted\_prefixes** are from a file called **deleted\_prefixes**.
  - (j) you have to write a function *search()* by giving an IP address to report if the search is successful or fails.
  - (k) Finally, you have to report average numbers of search, insert, delete clock cycles , draw three figures as follows.



## Command line:

> ./hw9 [d]

## Output:

**First**, print out the total number of prefixes in the “routing\_table.txt” to the screen.

**Second**, output the length distribution of prefixes in input file “routing\_table.txt” to a file named “length\_distribution”.

**Finally**, output the search result of those IPs in file “trace\_file.txt” to the three file “output\_1”, “output\_2”, “output3”.

(Note: **Don’t** print any unnecessary message to screen, thank you.)

In this homework, you must do the following

- (a) construct prefixes table in file “routing\_table.txt”.
- (b) insert prefixes in file “inserted\_prefixes.txt” after (a).
- (c) delete prefixes in “delete\_prefixes.txt” after (b).

output\_1: output the search result after (a)

output\_2: output the search result after (b)

output\_3: output the search result after (c)

## Score:

Total number of prefixes : 5%

Length distribution: 5%

Segment groups: 10%

Search : 25%

Insert : 20%

Delete : 20%

Report (Include figure mentioned above): 15%